

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/901,125	07/10/2001	Katsuya Demoto	1114-163	7206
23117 75	90 03/06/2006		EXAM	INER
NIXON & VANDERHYE, PC			HOSSAIN, TANIM M	
901 NORTH GLEBE ROAD, 11TH FLOOR ARLINGTON, VA 22203		JK	ART UNIT	PAPER NUMBER
,			2145	

DATE MAILED: 03/06/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

		<i></i>		
	Application No.	Applicant(s)		
0.00	09/901,125	DEMOTO, ET AL		
Office Action Summary	Examiner	Art Unit		
	Tanim Hossain	2145		
The MAILING DATE of this communicate Period for Reply	tion appears on the cover sheet wi	th the correspondence address		
A SHORTENED STATUTORY PERIOD FOR WHICHEVER IS LONGER, FROM THE MAIL - Extensions of time may be available under the provisions of 3' after SIX (6) MONTHS from the mailing date of this communic - If NO period for reply is specified above, the maximum statuto - Faillure to reply within the set or extended period for reply will, Any reply received by the Office later than three months after the earned patent term adjustment. See 37 CFR 1.704(b).	LING DATE OF THIS COMMUNIC 7 CFR 1.136(a). In no event, however, may a re- tation. ry period will apply and will expire SIX (6) MON by statute, cause the application to become AB	CATION. eply be timely filed ITHS from the mailing date of this communication. BANDONED (35 U.S.C. § 133).		
Status				
1) Responsive to communication(s) filed of	n <u>20 December 2005</u> .			
Pa) This action is FINAL . 2b) This action is non-final.				
3) Since this application is in condition for	· ·	·		
closed in accordance with the practice	under <i>Ex par</i> te Q <i>uayle</i> , 1935 C.D). 11, 453 O.G. 213.		
Disposition of Claims				
4)⊠ Claim(s) <u>1-23</u> is/are pending in the app	lication.			
4a) Of the above claim(s) is/are v	vithdrawn from consideration.			
5) Claim(s) is/are allowed.				
6)⊠ Claim(s) <u>1-23</u> is/are rejected.				
7) Claim(s) is/are objected to.				
8) Claim(s) are subject to restriction	n and/or election requirement.			
Application Papers				
9)☐ The specification is objected to by the E	xaminer.			
10) The drawing(s) filed on is/are: a)	accepted or b) objected to	by the Examiner.		
Applicant may not request that any objection	n to the drawing(s) be held in abeyan	nce. See 37 CFR 1.85(a).		
Replacement drawing sheet(s) including the	e correction is required if the drawing((s) is objected to. See 37 CFR 1.121(d).		
11)☐ The oath or declaration is objected to by	the Examiner. Note the attached	d Office Action or form PTO-152.		
riority under 35 U.S.C. § 119				
12) Acknowledgment is made of a claim for a) All b) Some * c) None of: 1. Certified copies of the priority doc		3 119(a)-(d) or (f).		
2. Certified copies of the priority do		pplication No		
3. Copies of the certified copies of t	he priority documents have been	received in this National Stage		
application from the International	Bureau (PCT Rule 17.2(a)).			
* See the attached detailed Office action for	or a list of the certified copies not	received.		
.ttachment(s)				
Notice of References Cited (PTO-892)	· —	Summary (PTO-413)		
 Notice of Draftsperson's Patent Drawing Review (PTO-) Information Disclosure Statement(s) (PTO-1449 or PTO Paper No(s)/Mail Date 		s)/Mail Date nformal Patent Application (PTO-152) 		

DETAILED ACTION

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claims 1-3, 5-8, 10, 11, and 14 are rejected under 35 U.S.C. 102(b) as being anticipated by Shaffer (E.P. 0,848,560).

As per claim 1, Shaffer teaches a communication system comprising: an information server capable of performing communication in first and second communication modes (column 4, lines 4-27; where one remotely located site constitutes the information server from which the user obtains data; column 5, lines 44-52); a communication apparatus capable of performing communication in the first and second communication modes (column 3, lines 9-16; column 4, lines 4-27), the communication apparatus including: communication circuitry capable of performing communication with the information server in the first and second communication modes (column 4, lines 4-27; column 3, lines 21-25; where one remote site constitutes one user, and the node from which data is obtained is the information server, and the network administrator controls the information server); a connection information storage section (column 6, line 56 – column 7, line 1; column 7, lines 20-28); a communication mode switching control section for controlling the switching of communication mode with the information server from

Page 3

the first communication mode to the second communication mode by storing into the connection information storage section connection information based on a condition of communication connection of the communication apparatus and the information server in the first communication mode at a time of the switching, releasing the connection of the communication circuitry with the information server in the first communication mode in a state in which a connection of the communication apparatus and the information server in the second communication mode is not established, establishing a connection with the information server in the second communication mode in a state in which a connection of the communication apparatus and the information server in the first communication mode is not established, and restoring the condition of communication connection, based on the stored connection information (column 3, lines 21-25; column 8, lines 3-22; column 10, lines 22-39, 55-59).

As per claim 2, Shaffer teaches the communication system of claim 1, wherein the communication apparatus further includes a switching condition storage section for storing a predetermined determination reference value, and wherein the communication mode switching control section compares an amount of information to be acquired from the information server and the determination reference, and determines whether or not to execute switching of communication mode, based on a result of the comparison (column 8, lines 3-22, 37-45).

As per claim 3, Shaffer teaches the communication system of claim 1, wherein the communication mode switching control section determines whether or not to execute the switching of communication mode, based on a kind of information to be acquired from the information server (column 3, lines 1-8; column 5, lines 53-55; where the medium based differences constitute switching by information type).

As per claim 5, Shaffer teaches the communication system of claim 1, wherein the communication apparatus further includes a switching condition storage section for storing a time (column 7, lines 20-28), and wherein the communication mode switching control section compares a current time and the time stored in the switching condition storage section, to determine whether or not to execute the switching of communication mode (column 3, lines 24-26; column 7, lines 20-37).

As per claim 6, Shaffer teaches the communication system of claim 1, wherein the communication mode switching control section determines whether to execute switching of communication mode or not, based on the operator's operation (column 11, line 34 – column 12, line 16; where the operator's choice of data implies a certain QoS, and when a suitable mode is found, the user chooses this, to initiate switching).

As per claim 7, Shaffer teaches the communication system of claim 1, wherein when a communication mode switching instruction is received from the information server, the communication mode switching control section switches the communication mode, based on the switching instruction (column 3, lines 24-25; where the network administrator's switch constitutes a switching instruction from the information server).

As per claim 8, Shaffer teaches the communication system of claim 7, wherein the communication apparatus transmits to the information server a signal representative of whether to transmit the communication mode switching instruction from the information server to the communication apparatus or not, based on the operator's operation (column 3, lines 24-25; column 6, lines 43-55; where the signal is inherently sent, by which the administrator can decide whether to switch modes by whether the QoS is met).

As per claim 10, Shaffer teaches a communication system comprising: an information server capable of performing communication in first and second communication modes (column 4, lines 4-27; where one remotely located site constitutes the information server from which the user obtains data; column 5, lines 44-52); and a communication apparatus capable of performing communication in the first and the second communication modes (column 3, lines 9-16; column 4, lines 4-27), the communication apparatus including: communication circuitry capable of performing communication with the information server in the first and the second communication modes (column 4, lines 4-27; where one remote site constitutes one user, and the node from which data is obtained is the information server); a connection information storage section (column 6, line 56 – column 7, line 1; column 7, lines 20-28); a switching condition storage section for storing a reference value of an information transfer rate (column 6, lines 18-30); and a communication mode switching control section for, when the communication means is acquiring information from the information server in the first communication mode monitoring a rate of information transfer from the information server, comparing the information transfer rate being monitored and the reference value of the information transfer rate previously stored in the switching condition storage section, and in cases where the information transfer rate being monitored does not exceed the reference value, storing a condition of communication connection with the information server at that time into the connection information storage section as the connection information, disconnecting the communication in the first communication mode in a state in which a connection of the communication apparatus and the information server in the second communication mode is not established, establishing a connection with the information server in the second communication mode to perform switching of communication mode in a

state in which a connection of the communication apparatus and the information server in the first communication mode is not established, and restoring the communication connection condition based on the connection information stored in the connection information storage section when the communication in the first communication mode is disconnected (column 6, lines 18-55; where the switching constitutes the disconnection from the first communication mode).

As per claim 11, Shaffer teaches a communication system comprising: an information server capable of performing communication in first and second communication modes (column 4, lines 4-27; where one remotely located site constitutes the information server from which the user obtains data; column 5, lines 44-52); and a communication apparatus capable of performing communication in the first and the second communication modes (column 3, lines 9-16; column 4, lines 4-27), the information server including: communication means capable of performing communication with the communication apparatus in the first and the second communication modes (column 4, lines 4-27; where one remote site constitutes one communication apparatus, and the node from which data is obtained is the information server); a switching condition storage section for storing a predetermined reference value of an information transfer rate (column 6, lines 18-30); and a communication mode switching control section for, when the communication means is transferring information to the communication apparatus in the first communication mode, monitoring the information transfer rate, comparing the information transfer rate being monitored and the reference value of the information transfer rate previously stored in switching condition storage section, and in cases where the information transfer rate being monitored does not exceed the reference value, causing the communication means to

transmit a communication mode switching instruction to the communication apparatus (column 6, lines 18-55; where the switching constitutes the disconnection from the first communication mode), and the communication apparatus including: communication means capable of performing communication with the information server in the first and the second communication modes (column 3, lines 9-16; column 4, lines 4-27); a connection information storage section for storing a communication connection condition as connection information (column 6, line 56 – column 7, line 1; column 7, lines 20-28); and a communication mode switching control section for, when the communication means receives the communication mode switching instruction causing a condition of communication connection with the information server at that time to be stored in the connection information storage section as the connection information, based on the switching instruction, disconnecting the communication in the first communication mode in a state in which a connection of the communication apparatus and the information server in the second communication mode is not established, establishing a connection with the information server in the second communication mode to perform switching of communication mode in a state in which a connection of the communication apparatus and the information server in the first communication mode is not established, and restoring the communication connection condition based on the connection information stored when the communication in the first communication mode is disconnected (column 6, lines 18-55; where the switching constitutes the disconnection from the first communication mode; column 3, lines 21-25; column 10, lines 55-59; column 12, lines 10-15).

As per claim 14, Shaffer teaches the communication system of claim 1, wherein after a predetermined time has elapsed since the information acquisition in the second communication

mode is completed, the communication mode switching control section automatically disconnects the communication in the second communication mode, and again establishes a connection with the information server in the first communication mode to perform switching of communication mode (column 3, lines 21-26; where the link failure constitutes the completion of the acquisition of information in the second mode, and the reconnection constitutes a reconnection into the first mode).

As per claim 15, Shaffer teaches a communication apparatus for communicating with an information server using different communication modes, the communication apparatus comprising: a communication section for establishing communications with the information server in the different communication modes (column 4, lines 29-45); a storage section (column 9, lines 1-5); and a communication mode switching control section for controlling the switching of communication modes with the information server by storing connection information into the storage second based on a communication connection condition of the communication apparatus and the information server in a current communication mode, releasing the communication connection with the information server in a state in which a connection of the communication apparatus and the information server in the second communication mode is not established, and establishing a communication connection with the information server in another mode in a state in which a connection of the communication apparatus and the information server in any communication mode is not established and restoring the communication connection condition based on the stored connection information (column 4, lines 29-45).

As per claim 18, Shaffer teaches the communication apparatus of claim 15, wherein the communication mode switching control section controls the switching based on an instruction signal from the information server (column 4, lines 29-45).

As per claim 20, Shaffer teaches the communication apparatus of claim 15, wherein the communication mode switching control section controls the switching in accordance with a type of information to be acquired from the information server (column 5, lines 53-55).

As per claim 21, Shaffer teaches the communication apparatus of claim 15, wherein the communication mode switching control section controls the switching based at least in part on communication charges (Abstract).

As per claim 22, Shaffer teaches the communication apparatus of claim 15, wherein the communication mode switching control section controls the switching based on comparison between a current time and a specified time (column 7, lines 20-28).

As per claim 23, Shaffer teaches the communication apparatus of Icaim 15, wherein the communication mode switching section controls the switching based at least in part on an operator's instruction (column 8, lines 26-29).

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Application/Control Number: 09/901,125

Art Unit: 2145

Claim 4 is rejected under 35 U.S.C. 103(a) as being unpatentable over Shaffer in view of Kunz (U.S. 6,223,221).

Page 10

As per claim 4, Shaffer teaches the communication system of claim 1, wherein the communication apparatus includes a switching condition storage section (column 4, lines 44-52), and wherein when an information acquisition request is received from the operator, the communication mode switching control section measures a parameter, and determines whether to execute switching of communication mode or not based on the measured parameter for the communication connection times in the first and second communication modes, respectively, previously stored in the switching condition storage section (column 6, lines 18-55). Shaffer does not specifically teach that the measured parameter is the connection time. Kunz teaches an intelligence tool in a web browser that measures download and connection time to perform a certain task (column 2, lines 8-34). It would have been obvious to one of ordinary skill in the art to include the tool to measure connection time into the QoS monitoring device, in which modes are switched based on whether the Qos is met, as taught by Kunz in the system of Shaffer. The motivation for doing so lies in the fact that adding the parameter of connection time would allow for modes to be discriminated by this parameter, further diversifying the invention. Connection charges are often incurred by connection time, and thus the inclusion of this component would account for this fact, allowing the system to choose a cheaper mode for information transfer. Both inventions are from the same field of endeavor, namely the efficient transfer of data through a network.

Claim 9 is rejected under 35 U.S.C. 103(a) as being unpatentable over Shaffer in view of Watson (U.S. 6,631,409).

As per claim 9, Shaffer teaches the communication system of claim 1, but does not specifically teach the user's ability to override switching instructions from the information server. Watson teaches the user's ability to override default network settings (column 10, lines 27-38). It would have been obvious to one of ordinary skill in the art at the time of the invention to include the ability of a user to override the instruction from the information server, based on his/her preference, as taught by Watson in the system of Shaffer. The motivation for doing so lies in the fact that allowing the user to ultimately control his/her preferences for communication modes gives the user a further degree of freedom to add further efficiency and ease of use to the invention. Both inventions are from the same field of endeavor, namely the efficient use of network resources to allow for data transportation.

Claims 12 and 13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Shaffer in view of Davis (U.S. 5,583,922).

As per claim 12, Shaffer teaches the communication system of claim 1, but does not specifically teach the automatic disconnection of a communication mode, after the information acquisition in this mode has been completed. Davis teaches the switching from a data transmission back to voice mode in a communication system, once the data transmission is completed (column 7, lines 19-45). It would have been obvious to one of ordinary skill in the art at the time of the invention to include the ability to automatically return to a first mode after the use of the second mode has been completed, as taught by Davis in the system of Shaffer. The

motivation for doing so lies in the fact that there exists a need for the connection to revert back to its default node, in a situation where connection to a second node must be paid for, for example. To avoid overcharging, it is necessary for the mode to revert to the default mode after the task in the second mode is completed, so that there is no unnecessary connection time to the second mode. Both inventions are from the same field of endeavor, namely the use of a communication system employing different methods of communication.

As per claim 13, Shaffer teaches the communication system of claim 1, and teaches that the instruction to switch the communication mode can come from the information server (column 3, lines 21-25). Shaffer does not specifically teach the automatic disconnection and switching from a second communication mode to a first communication mode, triggered by the information server. Davis teaches the switching from a data transmission back to voice mode in a communication system, once the data transmission is completed (column 7, lines 19-45). It would have been obvious to one of ordinary skill in the art to include the ability to automatically return to a first mode after the use of the second mode has been completed, triggered by the information server, as taught by Davis in the system of Shaffer. The motivation for doing so lies in the fact that there exists a need for the connection to revert back to its default node, in a situation where connection to a second node must be paid for, for example. To avoid overcharging, it is necessary for the mode to revert to the default mode after the task in the second mode is completed, so that there is no unnecessary connection time to the second mode. Both inventions are from the same field of endeavor, namely the use of a communication system employing different methods of communication.

Claims 16 and 17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Shaffer.

As per claim 16, Shaffer teaches the communication apparatus of claim 15, but does not specifically teach the use of a URL as a connection information. It would have been obvious to one of ordinary skill in the art at the time of the invention to include this as a criteria, in light of the fact that the connection modes, in Shaffer's invention, are governed by data type and websites. Therefore, it would have been obvious to include the use of a URL as a criteria, since certain modes would be better suited for certain URLs. See also O'Neil, U.S. Patent 6,128,279, which discusses directing different URLs to different server modes.

As per claim 17, Shaffer teaches the communication apparatus of claim 15, but does not specifically teach that the communication system is embodied in a portable terminal. It would have been obvious to one of ordinary skill in the art at the time of the invention to include the ability to make the system part of a portable device. In light of Shaffer disclosing that there exists a network interface, embodied in a modem, to control communications over the network (column 6, lines 1-13), and also a computer to govern over the process (figure 2), it would have been obvious to one of ordinary skill in the art at the time of the invention to include the ability to use wireless modems on a portable computer in this capacity, which constitutes embodiment in a portable terminal.

Claim 19 is rejected under 35 U.S.C. 103(a) as being unpatentable over Shaffer in view of McLain (U.S. 6,493,758).

As per claim 19, Shaffer teaches the communication apparatus of claim 15, wherein the communication mode switching control section controls the switching based on a comparison

(column 2, lines 13-58). Shaffer does not specifically teach that this comparison is performed as a limit of a data amount to be acquired. McLain teaches the placing of a limit of data to be downloaded from the information server, such that if it exceeds a reference value, discontinuation will take place (column 7 line 32 – column 8 line 6). It would have been obvious to one of ordinary skill in the art at the time of the invention to place a download limit on a certain mode and switch to another once this limit has been met, as taught by McLain in the system of Shaffer. The motivation for doing so lies in the fact that placing a limit on a download will enable tariffs to be controlled, in the case that after a certain amount, the tariff increases. With the obvious modification, switching may take place before the increase, for the consumer to enjoy lower tariffs without concerns of time limitation online. Both inventions are from the same field of endeavor, namely the efficient transfer of information thorough a network.

Page 14

Response to Arguments

Applicant's arguments filed on December 20, 2005 have fully been considered, but are not persuasive.

As per claims 1, 10, and 15 a communication apparatus is claimed. Shaffer's communication equipment controls communication modes, stores information, and is capable of communicating with an information server. This constitutes a communication apparatus regardless of location. In regards to Applicant's contention that a connection continues to be established in a first mode after switching to the second mode, Examiner respectfully disagrees. In switching to a different mode, there is no means by which the device would remain connected Application/Control Number: 09/901,125 Page 15

Art Unit: 2145

in the first mode. This is evidenced by the fact that having two communication modes open simultaneously serves no purpose, especially if the user desires media which can not be served by the first mode. Further, column 10, lines 55-59 discuss the tearing down of one mode to switch to the next node. The very concept of switching necessitates that the communication modes are used on a one-or-the-other basis. Monitoring quality of service of multiple modes is not equivalent to having a session or connection established in this mode. Establishing a connection solely to monitor QoS would defeat the purpose of the invention. As far as the restoration of communication condition after switching to a different mode, the condition of connection is reestablished in the minimum QoS and maximum tariff desired after switching, which constitutes a restoration of a condition of communication connection. Further, previous criteria of previous connections are restored.

In regards to claim 11, in column 12 of Shaffer, it is discussed that a remote server entity sends a notification to the client, which instructs the client to switch into a communication mode.

This constitutes the information server sending a mode switching instruction.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Tanim Hossain whose telephone number is 571/272-3881. The examiner can normally be reached on 8:30 am - 5 pm.

Application/Control Number: 09/901,125 Page 16

Art Unit: 2145

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Jason Cardone can be reached on 571/272-3933. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Tanim Hossain
Patent Examiner
Art Unit 2145

JASON CARDONE SUPERVISORY PATENT EXAMINER